

Glycol Ether DPM

Gen. Variant: SDS_US_GHS

Version 1.4

Revision Date 03/05/2018

Print Date 05/24/2019

SDS No.: BE640

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Trade name : Glycol Ether DPM
CAS Number: : 34590-94-8
Chemical characterization : Propylene Glycol Ethers
Chemical name : Dipropylene Glycol Monomethyl Ether
Synonyms : DPM, Dipropylene Glycol Methyl Ether, DPGME

Identified uses : Solvent

Company Address

Lyondell Chemical Company
LyondellBasell Tower, Suite 300
1221 McKinney St.
P.O. Box 2583
Houston Texas 77252-2583

Company Telephone

Customer Service 888 777-0232
product.safety@lyb.com

Emergency telephone number

CHEMTREC USA 800-424-9300
LYONDELL 800-245-4532

E-mail address : product.safety@lyb.com
Responsible/issuing person

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids Category 4
Specific target organ systemic toxicity - single exposure Category 3

GHS Classification Scale (1= severe hazard; 4= slight hazard)

Label elements

Hazard symbols :



Signal word : Warning

Hazard Statements : H227 Combustible liquid.
H335 May cause respiratory irritation.

Precautionary Statements : **Prevention**
P210 Keep away from open flames/hot surfaces. - No

Glycol Ether DPM

Gen. Variant: SDS_US_GHS

Version 1.4

Revision Date 03/05/2018

Print Date 05/24/2019

SDS No.: BE640

smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No additional information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Substances****Ingredients**

Chemical name	CAS-No. EC-No.	Weight %	Component Type
Dipropylene Glycol Monomethyl Ether	34590-94-8	> 99.0 %	A

Key:

(A) Substance

4. FIRST AID MEASURES

General advice : Consult a physician/doctor if necessary.
Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.
Show this material safety data sheet to the doctor in attendance.

Glycol Ether DPM

Version 1.4

Revision Date 03/05/2018

Print Date 05/24/2019

SDS No.: BE640

- If inhaled : Remove to fresh air.
Keep patient warm and at rest.
Give oxygen or artificial respiration as needed.
Obtain emergency medical attention.
Prompt action is essential.
- In case of skin contact : Remove contaminated clothing as needed.
Wash skin thoroughly with mild soap and water.
Flush with lukewarm water for 15 minutes.
If sticky, use waterless cleaner first.
Seek medical attention if discomfort persists.
- In case of eye contact : Flush with plenty of water for at least 15 minutes, occasionally
lifting the upper and lower eyelids.
If eye irritation persists, consult a specialist.
- If swallowed : This material may be a slight health hazard if ingested in large
quantities.
If large quantity swallowed, give lukewarm water (pint/ 1/2 liter)
if victim completely conscious/alert.
Do not induce vomiting. Risk of damage to lungs exceeds
poisoning risk.
Obtain emergency medical attention.
- Notes to physician**
- Symptoms : High doses may cause CNS depression (fatigue, dizziness and
possibly loss of concentration, with collapse, coma and death in
cases of severe over-exposure).
- Hazards : May be harmful if swallowed and enters airways.
May cause respiratory irritation.
- Treatment : Treatment of overexposure should be directed at the control of
symptoms and the clinical condition of the patient.

5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, water spray or regular
foam. LARGE FIRE: Use water spray, water fog or regular
foam. Do not use straight streams.

Glycol Ether DPM

Gen. Variant: SDS_US_GHS

Version 1.4

Revision Date 03/05/2018

Print Date 05/24/2019

SDS No.: BE640

- Unsuitable extinguishing media : Do not use solid water stream.
- Specific hazards during fire fighting : Heat from fire can generate flammable vapor. When mixed with air and exposed to ignition source, vapors can burn in open or explode if confined. Flammable vapors may be heavier than air and travel long distances along the ground before igniting and flashing back to vapor source. Fine sprays/mists may be combustible at temperatures below normal flash point. Heat may build enough pressure to rupture closed containers/spreading fire/increasing risk of burns/injuries. Cool containers with flooding quantities of water until well after fire is out. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Move containers from fire area if it can be done without risk. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : Wear an approved positive pressure self-contained breathing apparatus and firefighter turnout gear. Structural firefighter's protective clothing will only provide limited protection.
- Further information : Cool containers with flooding quantities of water until well after fire is out.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Use personal protective equipment. Eliminate all sources of ignition. Clean-up to be performed only by trained and properly equipped personnel.
- Methods for containment / Methods for cleaning up : Eliminate all sources of ignition. All equipment used when handling this product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors.

Glycol Ether DPM

Version 1.4

Revision Date 03/05/2018

Print Date 05/24/2019

SDS No.: BE640

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Use clean non-sparking tools to collect absorbed material.

Additional advice : Keep non-involved personnel away from the area of spillage. See section 8 for additional PPE information. See section 13 for disposal information.

7. Handling and storage**Precautions for safe handling**

Advice on safe handling : Keep container tightly closed when not in use. The potential for peroxide formation is enhanced when this solvent is used in processes such as distillation. Use only non-sparking tools. Properly ground containers before beginning transfer. When transferring propylene glycol ethers with flash points at or below 60 °C (140 °F) into fixed site vessels, the vessel should be purged and inerted prior to transfer. Propylene glycol ethers may be transferred into air atmospheres if the temperature of the product and the ambient temperature within the shipping container are both at least 16.7 °C (30 °F) less than the product's flash point. After loading, nitrogen blanketing is required if the contents of the transportation container could exceed a temperature of 16.7 °C (30 °F) less than the product flash point during any subsequent transportation activities. If the product flash point is less than 16.7 °C (30 °F) above either the ambient temperature of the transportation container or the storage temperature of the product, the container should be purged and inerted with nitrogen prior to loading and nitrogen blanketed after loading. Handle empty containers with care. Flammable/combustible residue remains after emptying. The purging of all empty shipping containers, regardless of the flashpoint, is recommended when received with air atmospheres. Isolate, vent, drain, wash and purge systems or equipment before maintenance or repair. Use adequate personal protective equipment. Observe precautions pertaining to confined space entry.

Fire-fighting class : OSHA/NFPA Class IIIA Combustible Liquid.

Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store only in tightly closed, properly vented containers away from heat, sparks, open flame and strong oxidizing agents.

Glycol Ether DPM

Gen. Variant: SDS_US_GHS

Version 1.4

Revision Date 03/05/2018

Print Date 05/24/2019

SDS No.: BE640

Storage under nitrogen atmosphere is recommended to minimize potential for moisture condensation in the vapor space, and the formation of peroxides.
 Store in properly lined steel/stainless steel to avoid slight discoloration from mild steel/copper.
 Aluminum (5000 series alloys - U.S. Aluminum Association Standard) showed no corrosion after 30 days contact with PM Acetate, DPM, TPM, PTB, or PM at 71°C (160°F).
 Some plastics/rubbers are attacked by Glycol Ethers/Ether Esters.
 This product will absorb water if exposed to air.

Advice on common storage : Carbon steel
 Store in properly lined steel/stainless steel to avoid slight discoloration from mild steel/copper.
 Some plastics/rubbers are attacked by Glycol Ethers/Ether Esters.

Other data : Stable under recommended storage conditions.

Specific end use(s)
 : See Section 1.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters****Ingredients with workplace control parameters****Occupational Exposure Limits**

Ingredients	CAS-No.	Type	Limit Value	Basis Revision Date	Additional Information
Dipropylene Glycol Monomethyl Ether	34590-94-8	STEL	150 ppm	US (ACGIH) 2012	
Dipropylene Glycol Monomethyl Ether	34590-94-8	TWA	100 ppm	US (ACGIH) 2012	
Dipropylene Glycol Monomethyl Ether	34590-94-8	IDLH	600 ppm	NIOSH September 2007	
Dipropylene Glycol Monomethyl Ether	34590-94-8	TWA	100 ppm 600 mg/m ³	US (OSHA) June 23, 2006	

Consult local authorities for acceptable exposure limits.

Glycol Ether DPM

Version 1.4

Revision Date 03/05/2018

Print Date 05/24/2019

SDS No.: BE640

Exposure controls**Engineering measures**

Local exhaust in addition to general room ventilation may be required to meet exposure limit(s).

Personal protective equipment

- Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
If exposure can exceed the occupational exposure limit(s), use approved respiratory protection equipment.
- Hand protection : Wear chemical resistant gloves such as:
Neoprene.
- Eye and face protection : Use splash goggles when eye contact due to splashing or spraying liquid is possible.
- Skin and body protection : Depending on the conditions of use, protective gloves, apron, boots, head and face protection should be worn.
Use PPE that is chemical resistant to the product and prevents skin contact.
- Hygiene measures : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Use good personal hygiene practices.
Wash hands before eating, drinking, smoking, or using toilet facilities.
Take off contaminated clothing and wash before reuse.
Use care in walking on spilled material.
- Protective measures : Wear suitable protective equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : Clear, colorless.
- Odor : Ether-like odor.
- Odor Threshold : No Data Available.
- Flash point : 75 °C
at 1,013 hPa (760 mm Hg)
- Ignition temperature : 206.5 °C
at 1,013 hPa
- Lower explosion limit : 1.1 vol%

Glycol Ether DPM

Gen. Variant: SDS_US_GHS

Version 1.4

Revision Date 03/05/2018

Print Date 05/24/2019

SDS No.: BE640

Upper explosion limit	: 14 vol%
Flammability (solid, gas)	: Not applicable
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: 206.5 °C at 1,013 hPa
Molecular weight	: 148.2 g/mol
Decomposition temperature	: not determined
Melting point/freezing point	: -83 °C at 1,013 hPa
Boiling point/boiling range	: 189.6 °C at 1,013 hPa
Vapor pressure	: ~ 0.37 hPa at 20 °C
Density	: 0.95 g/cm ³ at 20 °C
Water solubility	: 25 °C completely miscible
Partition coefficient: n-octanol/water	: log Pow: 0.004 at 25 °C
Viscosity, dynamic	: 4.000 mPa.s at 25 °C (Brookfield).
Viscosity, kinematic	: 4.55 mm ² /s at 20 °C (static)
Relative vapor density	: ~ 5.1 at 16 - 32 °C (Air = 1.0)
Evaporation rate	: 0.02 (butyl acetate = 1)
Explosive properties	: Not explosive
Other Information	: Hygroscopic.

Glycol Ether DPM

Version 1.4

Revision Date 03/05/2018

Print Date 05/24/2019

SDS No.: BE640

10. STABILITY AND REACTIVITY

- Reactivity** : Will not occur.
- Chemical stability** : Stable under recommended storage conditions.
- Hazardous reactions** : Will not occur.
- Conditions to avoid** : Extended contact with air or oxygen.
The potential for peroxide formation is enhanced when this solvent is used in processes such as distillation.
Heat, sparks, open flame, other ignition sources, and oxidizing conditions.
Ignition may occur at temperatures below those published in the literature as autoignition or ignition temperatures.
- Materials to avoid** : Air or oxygen.
Moisture and humidity.
Strong oxidizing agents.
May react with oxygen to form peroxides.
- Hazardous decomposition products** : Not expected to decompose under normal conditions.
- Thermal decomposition** : Carbon Monoxide and other toxic vapors.

11. TOXICOLOGICAL INFORMATION

- Product Summary** : The below given information is based on the assessment of the product including impurities.
- Acute toxicity**
- Acute oral toxicity** : Based on acute toxicity values, not classified.
Ingestion of very large amounts may cause CNS depression, respiratory failure, and death in cases of severe over-exposure.
- : LD50: > 5,000 mg/kg
Species: Rat
- Acute inhalation toxicity** : Based on acute toxicity values, not classified.
May cause mild CNS depression.
Exposure to vapor may cause irritation of the eyes, nose, or throat.
- : LC50: > 275 ppm
Exposure time: 7 HOURS
Species: Rat

Glycol Ether DPM

Gen. Variant: SDS_US_GHS

Version 1.4

Revision Date 03/05/2018

Print Date 05/24/2019

SDS No.: BE640

- Acute dermal toxicity** : Based on acute toxicity values, not classified.
: LD50: > 9,500 mg/kg
Species: Rat
- Skin corrosion/irritation** : Based on skin irritation values, not classified.
- Serious eye damage/eye irritation** : Based on eye irritation values, not classified.
- Respiratory or skin sensitization** : Respiratory sensitization
no data available
No study available.
: Skin sensitization
no data available
No adverse effect observed.
- Chronic toxicity**
- Carcinogenicity : Not classified
No adverse effect observed.
- Germ cell mutagenicity : Not classified
No adverse effect observed.
- Reproductive toxicity**
- Effects on fertility / : Not classified
Effects on or via lactation : No adverse effect observed.
- Effects on Development : Not classified
No adverse effect observed.
- Target Organ Systemic Toxicant - Single exposure** : Classified
: May cause respiratory irritation.
: Exposure routes: Inhalation
- Target Organ Systemic Toxicant - Repeated exposure** : Based on repeated exposure toxicity values, not classified.

Glycol Ether DPM

Gen. Variant: SDS_US_GHS

Version 1.4

Revision Date 03/05/2018

Print Date 05/24/2019

SDS No.: BE640

Aspiration hazard : Not classified
May be harmful if swallowed and enters airways.

12. Ecological information**Ecotoxicology Assessment**

Acute aquatic toxicity : Based on acute aquatic toxicity values, not classified.

Chronic aquatic toxicity : Not classified, based on readily biodegradability and low acute toxicity.

Toxicity to fish : Low acute toxicity to fish

Toxicity to daphnia and other aquatic invertebrates : Low acute toxicity to aquatic invertebrates.

Toxicity to algae : Low toxicity to algae.

Toxicity to bacteria : Low toxicity to sewage microbes.

Toxicity to fish (Chronic toxicity) : no data available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Low chronic toxicity to aquatic invertebrates.

Persistence and degradability

Biodegradability : Biodegradation: 76 - 92 %
Rapidly degradable.
(After 28 days in a ready biodegradability test)

Bioaccumulative potential

Bioaccumulation : This material is not expected to bioaccumulate.

Mobility in soil

Distribution among environmental compartments : Type: Stability in water
no data available

: Type: Stability in soil
no data available
Low absorption to soil particulates predicted

Glycol Ether DPM

Gen. Variant: SDS_US_GHS

Version 1.4

Revision Date 03/05/2018

Print Date 05/24/2019

SDS No.: BE640

Other adverse effects**Environmental fate and pathways** : No additional information available.**Other information****Additional ecological information** : No additional information available.**13. Disposal considerations****Waste treatment methods**

Product : Contaminated product, soil, or water may be hazardous waste.
Dispose of contents/ container to an approved landfill.
Use registered transporters.
Burn concentrated liquids.
Assure emissions comply with applicable regulations.
Dilute aqueous waste may biodegrade.
Avoid overloading/poisoning plant biomass.
Assure effluent complies with applicable regulations.

Contaminated packaging : Do not burn, or use a cutting torch on, the empty drum.
Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

Not regulated for transport

CFR_ROAD

UN number : NA1993
Description of the goods : COMBUSTIBLE LIQUID, N.O.S.
: (DIPROPYLENE GLYCOL METHYL ETHER)
Class : CL
Packing group : III
Labels : 3

Marine pollutant : no

CFR_RAIL

UN number : NA1993
Description of the goods : COMBUSTIBLE LIQUID, N.O.S.
: (DIPROPYLENE GLYCOL METHYL ETHER)
Class : CL
Packing group : III

Glycol Ether DPM

Gen. Variant: SDS_US_GHS

Version 1.4

Revision Date 03/05/2018

Print Date 05/24/2019

SDS No.: BE640

Labels : 3

Marine pollutant : no

BLG (MARPOL Annex II)

Description of the goods : POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6)ETHER (CONTAINS DIPROPYLENE GLYCOL METHYL ETHER)

Pollution category : Z

Ship type : 3

15. REGULATORY INFORMATION

If identified components of this product are listed under the TSCA 12(b) Export Notification rule, they will be listed below. Export notification required.

TSCA 12b

Dipropylene Glycol Monomethyl Ether / CAS# 34590- TSCA section 4 94-8.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Physical Hazards

Flammable liquids

Health Hazards

Specific target organ systemic toxicity - single exposure

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material is not known to contain a chemical substance known to the State of California to cause cancer, reproductive, or developmental toxicity under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains the following chemicals regulated by New Jersey's Worker and Community

Glycol Ether DPM

Gen. Variant: SDS_US_GHS

Version 1.4

Revision Date 03/05/2018

Print Date 05/24/2019

SDS No.: BE640

Right to Know Act:

34590-94-8 Dipropylene Glycol Monomethyl Ether

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

34590-94-8 Dipropylene Glycol Monomethyl Ether

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

34590-94-8 Dipropylene Glycol Monomethyl Ether

Other international regulations**Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

REACH status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that the chemical substance in this product has been pre-registered or, where required under REACH, registered, and that we have the intention to proceed with any required registration in accordance with the deadlines set forth in REACH. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Glycol Ether DPM

Version 1.4

Revision Date 03/05/2018


Print Date 05/24/2019

SDS No.: BE640


Material safety datasheet sections which have been updated:

Revised Section(s): 15 February 27 2018

HMIS Classification : Health Hazard: 2
Flammability: 2
Physical hazards: 0



NFPA Classification : Health Hazard: 2
Fire Hazard: 2
Instability: 0

**Further information**

HMIS rating scale (0 = minimal hazard; 4 = severe hazard)

NFPA rating scale (0 = minimal hazard; 4 = severe hazard)

Disclaimer

This document is generated for the purpose of distributing health, safety, and environmental data.

Information is correct to the best of our knowledge at the date of the SDS publication.

It is not a specification sheet nor should any displayed data be construed as a specification.

Before using a product sold by a company of the LyondellBasell family of companies, users should make their own independent determination that the product is suitable for the intended use and can be used safely and legally.

SELLER MAKES NO WARRANTY; EXPRESS OR IMPLIED (INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY WARRANTY) OTHER THAN AS SEPARATELY AGREED TO BY THE PARTIES IN A CONTRACT.

Users should review the applicable Safety Data Sheet before handling the product.

This product(s) may not be used in the manufacture of any of the following, without prior written approval by Seller for each specific product and application:

- (i) U.S. FDA Class I or II Medical Devices; Health Canada Class I, II or III Medical Devices; European Union Class I or II Medical Devices;
- (ii) film, overwrap and/or product packaging that is considered a part or component of one of the aforementioned medical devices;
- (iii) packaging in direct contact with a pharmaceutical active ingredient and/or dosage form that is intended for inhalation, injection, intravenous, nasal, ophthalmic (eye), digestive, or topical (skin) administration;
- (iv) tobacco related products and applications, electronic cigarettes and similar devices.
- (v) safety components in automotive applications, for example: air bags, air bag unit housings and covers, seat belt mechanisms, brake systems, pedals and pedal supports, steering systems.

The product(s) may not be used in:

Glycol Ether DPM

Gen. Variant: SDS_US_GHS

Version 1.4

Revision Date 03/05/2018

Print Date 05/24/2019

SDS No.: BE640

Disclaimer

- (i) U.S. FDA Class III Medical Devices; Health Canada Class IV Medical Devices; European Class III Medical Devices;
- (ii) applications involving permanent implantation into the body;
- (iii) life-sustaining medical applications.

All references to U.S. FDA, Health Canada, and European Union regulations include another country's equivalent regulatory classification.

In addition to the above, LyondellBasell may further prohibit or restrict the use of its products in certain applications. For further information, please contact a LyondellBasell representative.

Alkylate, Duopac, Duoprime, Filmex, MPDIOL, Polymeg, SAA-100, SAA-101, TBAC, Tebol, T-Hydro, and Tufflo are trademarks owned or used by the LyondellBasell family of companies. Duopac, Duoprime, Filmex, MPDIOL, Polymeg, Tebol, T-Hydro and Tufflo are registered in the U.S. Patent and Trademark Office.

Product Information

HMIS rating scale (0 = minimal hazard; 4 = severe hazard) NFPA rating scale (0 = minimal hazard; 4 = severe hazard)

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet